

Appln No. 09/618,965

Amdt date December 24, 2003

Reply to Office action of October 9, 2003

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Currently Amended) A method for interactive debugging comprising:

selecting a target construct for debugging;  
accessing data related to an operation of the target construct by a debug construct in real time; [[and]]  
monitoring at least a portion of the accessed data without disturbing the operation of the target construct [[to]]; and  
debugging the target construct using the monitored portion of the accessed data.

2. (Original) The method of claim 1 further comprising modifying at least a portion of the data.

3. (Original) The method of claim 1 wherein the target construct is one selected from the group consisting of a service, a socket, a service stack, a set of services, and a set of sockets.

4. (Original) The method of claim 1 wherein the debug construct comprises at least one service, at least one socket, or a combination of at least one service and at least one socket.

5. (Original) The method of claim 1 wherein selecting a target construct further comprises:

Appln No. 09/618,965

Amdt date December 24, 2003

Reply to Office action of October 9, 2003

providing information about a plurality of services; and  
selecting the target construct from the plurality of  
services.

6. (Original) The method of claim 5 wherein the  
information includes a current state of each of the plurality of  
services.

7. (Original) The method of claim 5 further  
comprising:

providing information about a plurality of sockets;  
and

selecting the target construct from the plurality of  
sockets.

8. (Original) The method of claim 7 wherein the  
information includes a current state of each of the plurality of  
services.

9. (Original) The method of claim 1 further  
comprising accessing a memory of the target construct by the  
debug construct, the accessing corresponding to reading the  
memory or writing to the memory.

10. (Original) The method of claim 1 further  
comprising accessing state of the target construct by the debug  
construct, the accessing corresponding to reading the state or  
modifying the state.

11. (Original) The method of claim 1 further  
comprising dynamically allocating the debug construct.

Appln No. 09/618,965

Amdt date December 24, 2003

Reply to Office action of October 9, 2003

12. (Original) The method of claim 1 further comprising dynamically de-allocating the debug construct once the monitoring is completed.

13. (Original) The method of claim 1 further comprising collecting statistics related to the target construct.

14. (Original) The method of claim 1 further comprising transmitting the data to at least one host system.

15. (Original) The method of claim 14 wherein the data is transmitted based upon a request sent by a host application.

16. (Original) The method of claim 14 wherein an operating system determines which data is to be transmitted.

17. (Original) The method of claim 14 wherein the debug construct specifies which data is to be transmitted.

18. (Original) The method of claim 1 further comprising notifying the debug construct upon a completion of a certain operation by the target construct.

19. (Original) The method of claim 14 further comprising:  
measuring bandwidth required to transmit the data; and  
transmitting at least a portion of data based upon available bandwidth.

20. (Original) The method of claim 1 wherein debugging is performed in a multi-channel, multi-service environment.

Appln No. 09/618,965

Amdt date December 24, 2003

Reply to Office action of October 9, 2003

21. (Original) The method of claim 15 wherein sending the request and transmitting the response are performed over a network.

22. (Original) The method of claim 1 further comprising:

collecting at least a portion of the data;  
allocating a copy of the target construct in a simulated environment; and  
debugging the operation of the target construct using the collected data in the simulated environment.

23. (Original) The method of claim 1 further comprising:

generating a request by a host application;  
transmitting the request to an operating system;  
performing the request by the operating system; and  
sending a response to the host application.

24. (Currently Amended) A method for multi-channel, multi-service debugging, comprising:

providing information about ~~at least one~~ a plurality of running services;  
maintaining an isolated debugging environment for each of the ~~at least one~~ plurality of running services; and  
selecting a target construct for debugging from the ~~at least one~~ plurality of running services.

25. (Currently Amended) The method of claim 24 wherein the information about the ~~at least one~~ plurality of running services includes a current state of each service.

Appln No. 09/618,965

Amdt date December 24, 2003

Reply to Office action of October 9, 2003

26. (Original) The method of claim 24 further comprising:

providing information about at least one socket;  
maintaining an isolated debugging environment for each of the at least one socket; and  
selecting a target construct for debugging from the at least one socket.

27. (Original) The method of claim 26 wherein the information about the at least one socket includes a current state of each socket.

28. (Original) The method of claim 24 wherein the target construct is one selected from the group consisting of a service, a socket, a service stack, a set of services, and a set of sockets.

29. (Original) The method of claim 28 further comprising switching between services and sockets during a debugging process.

30. (Original) The method of claim 24 wherein the isolated debugging environment is maintained by an operating system in cooperation with a host application.

31. (Original) The method of claim 24 wherein the target construct is selected based upon a request from a host application.

32. (Original) The method of claim 24 further comprising:

generating a request by a host application;

Appln No. 09/618,965

Amdt date December 24, 2003

Reply to Office action of October 9, 2003

transmitting the request to an operating system;  
performing the request by the operating system; and  
sending a response to the host application.

33. (Original) The method of claim 32 wherein transmitting the request and sending a response are performed over a network.

34. (Original) The method of claim 24 further comprising:  
sending a request by a host application; and  
receiving a response by the host application once a requested operation is completed.

35. (Original) The method of claim 34 wherein sending a request and receiving a response are performed over a network.

36. (Original) The method of claim 24 further comprising:  
receiving a request by an operating system;  
performing a requested operation; and  
transmitting a response once the requested operation is completed.

37. (Original) The method of claim 36 wherein receiving a request and transmitting a response are performed over a network.

38. (Original) The method of claim 24 further comprising dynamically allocating at least one service into the target construct.

Appln No. 09/618,965

Amdt date December 24, 2003

Reply to Office action of October 9, 2003

39. (Original) The method of claim 38 further comprising instantiating any of at least one service, at least one service stack, and at least one socket.

40. (Original) The method of claim 24 further comprising substituting input and output data for at least one socket.

41. (Original) The method of claim 40 further comprising:

collecting data for at least one socket;

allocating a copy of the target construct in a simulated environment; and

debugging the operation of the target construct using the collected data.

42. (Currently Amended) An apparatus for interactive debugging comprising:

means for selecting a target construct for debugging;

means for accessing data related to an operation of the target construct by a debug construct in real time; [[and]]

means for monitoring at least a portion of the accessed data without disturbing the operation of the target construct; and

debugging the target construct using the monitored portion of the accessed data.

43. (Currently Amended) An apparatus for multi-channel, multi-service debugging, comprising:

means for providing information about at least one a plurality of running services;

Appln No. 09/618,965

Amdt date December 24, 2003

Reply to Office action of October 9, 2003

means for maintaining an isolated debugging environment for each of the ~~at least one~~ plurality services; and

means for selecting a target construct for debugging from the ~~at least one~~ plurality of running services.

44. (Original) An apparatus for interactive debugging comprising:

a target construct; and

a debug construct configured to access data related to an operation of the target construct in real time and to monitor at least a portion of the data without disturbing the operation of the target construct.

45. (Original) The apparatus of claim 44 wherein the debug construct is further configured to modify at least a portion of the data.

46. (Original) The apparatus of claim 44 wherein the target construct is one selected from the group consisting of a service, a socket, a service stack, a set of services, and a set of sockets.

47. (Original) The apparatus of claim 44 wherein the debug construct comprises at least one service, at least one socket, or a combination of at least one service and at least one socket.

48. (Original) The apparatus of claim 44 further comprising a user interface for providing information about a plurality of services and selecting the target construct from the plurality of services upon a user request.



Appln No. 09/618,965

Amdt date December 24, 2003

Reply to Office action of October 9, 2003

49. (Original) The apparatus of claim of claim 48 wherein the information about a plurality of services includes a current state of each of the plurality of services.

50. (Original) The apparatus of claim 48 wherein the user interface further provides information about a plurality of sockets and allows the user to select the target construct from the plurality of sockets.

51. (Original) The apparatus of claim of claim 50 wherein the information about a plurality of sockets includes a current state of each of the plurality of sockets.

52. (Original) The apparatus of claim 48 wherein the user interface is a text-based interface or graphical user interface.

53. (Original) The apparatus of claim 44 further comprising a platform control socket configured to dynamically allocate the debug construct.

54. (Original) The apparatus of claim 44 further comprising a platform control socket further configured to dynamically de-allocate the debug construct once the monitoring is completed.

55. (Original) The apparatus of claim 44 further comprising a profiler collecting statistics related to the target construct.

56. (Original) The apparatus of claim 44 further comprising:

Appln No. 09/618,965

Amdt date December 24, 2003

Reply to Office action of October 9, 2003

at least one host processor; and  
a communications infrastructure for transmitting the data to the host processor.

57. (Original) The apparatus of claim 56 further comprising an operating system configured to determine which data is to be transmitted, measure bandwidth required to transmit the data, and determine a portion of the data to be transmitted based upon available bandwidth.

58. (Original) The apparatus of claim 56 wherein the debug construct is further configured to specify which portion of the data is to be transmitted.

59. (Original) The apparatus of claim 56 wherein the data is transmitted based upon the request sent by a host application.

60. (Original) The apparatus of claim 44 wherein debugging is performed in a multi-channel, multi-service environment.

61. (Original) The apparatus of claim 56 further comprising:

a host application generating a request;  
a communications infrastructure transmitting the request to the debug construct; and  
the debug construct configured to perform the request and to send a response to the host application.

62. (Original) The apparatus of claim 61 wherein the communications infrastructure is a network.

Appln No. 09/618,965

Amdt date December 24, 2003

Reply to Office action of October 9, 2003

63. (Original) The apparatus of claim 56 further comprising a host application sending a request and receiving a response once a requested operation is completed.

64. (Original) The apparatus of claim 63 wherein the host application sends a request and receives a response over a network.

65. (Original) The apparatus of claim 56 wherein the debug construct is further configured to receive a request, perform a requested operation, and transmit a response once the requested operation is completed.

66. (Original) The apparatus of claim 65 wherein the debug construct receives the request and transmits the response over a network.

67. (Currently Amended) An apparatus for multi-channel, multi-service debugging, comprising:  
a graphical user interface for providing information about ~~at least one~~ a plurality of running services;  
an operating system maintaining an isolated debugging environment for each of the ~~at least~~ plurality of running services; and  
a debug core configured to select a target construct for debugging from the ~~at least one~~ plurality of running services upon a user request.

68. (Original) The apparatus of claim 67 wherein the information about the at least one service includes a current state of each service.

Appln No. 09/618,965

Amdt date December 24, 2003

Reply to Office action of October 9, 2003

69. (Original) The apparatus of claim 67 wherein the graphical user interface provides information about at least one socket, the operating system maintains an isolated debugging environment for each of the at least socket, and the debug core is configured to select a target construct for debugging from the at least one socket upon a user request.

70. (Original) The apparatus of claim 69 wherein the information about the at least one socket includes a current state of each socket.

71. (Original) The apparatus of claim 67 wherein the target construct is one selected from the group consisting of a service, a socket, a service stack, a set of services, and a set of sockets.

72. (Original) The apparatus of claim 67 wherein the debug core is further configured to switch between services and sockets during a debugging process upon a user request.

73. (Original) The apparatus of claim 67 further comprising a host application configured to send a request to select the target construct.

74. (Original) The apparatus of claim 73 further comprising:

a communications infrastructure transmitting the request to an operating system; and

the operating system configured to perform the request.

Appln No. 09/618,965

Amdt date December 24, 2003

Reply to Office action of October 9, 2003

75. (Original) The apparatus of claim 74 wherein the communications infrastructure is a network.

76. (Original) The apparatus of claim 67 further comprising a host application sending a request for a debugging operation and receiving a response once the operation is completed.

77. (Original) The apparatus of claim 67 wherein the operating system receives a request for a debugging operation, performs the operation, and transmits a response once the requested operation is completed.

78. (Original) The apparatus of claim 67 further comprising a host application requesting to dynamically allocate at least one service into the target construct and to instantiate at least one service or at least one service stack.

79. (Original) The apparatus of claim 67 wherein a host application cooperates with the operating system to substitute input and output data for at least one socket.

80. (Original) The apparatus of claim 79 wherein the host application is configured to request to collect data for at least one socket, to allocate a copy of the target construct in a simulated environment, and to debug the operation of the target construct using the collected data in the simulated environment.

81. (Currently Amended) A system for interactive debugging, comprising:

Appln No. 09/618,965

Amdt date December 24, 2003

Reply to Office action of October 9, 2003

a memory configured to store data related to an operation of a target construct; and

at least one processor coupled to the memory, the processor configured to select the target construct for debugging, access the data in the memory in real time, and monitor at least a portion of the accessed data from the memory without disturbing the operation of the target construct to debug the target construct using the monitored portion of the accessed data.

82. (Currently Amended) A system for multi-channel, multi-service debugging, comprising:

a memory configured to store information about a plurality of running at least one services; and

at least one processor coupled to the memory, the processor configured to maintain an isolated debugging environment for each of the at least one plurality of running services and to provide a capability to view the information stored on the memory and to select a target construct for debugging from the information.

83. (Currently Amended) A computer readable medium comprising instructions, which when executed on a processor, perform a method for interactive debugging comprising:

selecting a target construct for debugging;

accessing data related to an operation of the target construct by a debug construct in real time; [[and]]

monitoring at least a portion of the accessed data without disturbing the operation of the target construct [[to]]; and

debugging the target construct using the monitored portion of the accessed data.

Appln No. 09/618,965

Amdt date December 24, 2003

Reply to Office action of October 9, 2003

84. (Currently Amended) A computer readable medium comprising instructions, which when executed on a processor, perform a method for multi-channel, multi-service debugging, comprising:

providing information about ~~at least one~~ a plurality of running services;

maintaining an isolated debugging environment for each of the ~~at least one~~ plurality of running services; and

selecting a target construct for debugging from ~~[[a]]~~ the plurality of running services.

---